

Amended Claims

24
1. A method for password enhancing, which method comprises the steps of entering a user password and irreversibly encrypting the user password.

25
2. A method according to claim 1, in which the encryption comprises a hash operation.

26
3. A method according to claim 1, in which the method comprises the additional step of using an encrypted first stored key (NEPKEY) to encrypt the irreversibly encrypted user password (HASH).

27
4. A method according to claim 3, in which the first stored key is encrypted by a public key encryption algorithm.

28
5. A method according to claim 3, in which the method comprises the additional step of decrypting an encrypted second stored key (UPEK) using the decrypted first stored key (NEPKEY).

29
6. A method according to claim 5, in which the second stored key is encrypted by a reversible algorithm.

30

7. A method according to claim 5, in which the result (HASH) of the irreversibly encrypted user password is encrypted using the second stored key (UPEK) as an encryption key.

30

30

8. A data access method comprising the steps of producing an enhanced password according to claim 7, comparing the enhanced password with a password associated with the data, and permitting access to the data only if the enhanced password and the data password correspond.

A2

34

9. A computer program for carrying out the method of claim 8.

33

30

10. A carrier comprising a program according to claim 9.

34

34

11. A data communication system comprising an input device for generating a plurality of input signals available from a set of input signals and a character generator configured to receive an input signal and generate an output signal comprising a plurality of signals from the set of input signals in which the output signal is different from the signal input to the character generator.

37

12. A data communication system according to claim 11, in which the output signal is of a different length to the signal input to the character generator.

34

38

13. A data communication system according to claim 12, in which the output signal is longer than the signal input to the character generator.

37

39
14. A data communication system according to claim 11, in which the system further comprises means for comparing the output signal with a stored password.

40
15. A data communication system according to claim 14, in which the comparison means further comprises means for outputting a signal dependent upon the correspondence of the output signal with the stored password.

41
16. A data communication system according to claim 11, in which the input device comprises a keyboard.

42
17. A data communication system according to claim 16, in which the set of available input signals comprises all or part of the character set of the keyboard.

43
18. A data communication system according to claim 11, in which the system comprises a first input and a second input in which the character generator receives signals from the first input and does not receive signals from the second input.

44
19. A data communication system according to claim 18, in which the first input is a local input device such as a keyboard or microphone and the second input is a remote based input device typically providing signals via a modem connection.

45
20. A data communication system according to claim 19, in which the input signal comprises or corresponds to one of the set of input signals.

⁴⁶
21. A data communication system according to claim ⁴⁵20, in which the set of input signals comprises alphanumeric characters.

A2 ⁴⁷
22. A digital computer comprising a data communication system according to claim ⁴⁶21.

21.26 ⁴⁸
23. A data communication method comprising receiving an input signal available from a set of input signals, generating an output signal comprising a plurality of signals from the set of available input signals, in which the output signal is different from the input signal.

⁴⁹
24. A method according to claim ⁴⁸23, in which the method further comprises the step of repeating the operation for a plurality of input signals.

⁵⁰
25. A method according to claim ⁴⁸23, in which the output signals vary in length one from the other.
